

Intelligence Handbook

Soviet Strategic Weapons: Background for SALT

Secret

SR IH 69-4 October 1969

ARCHIVAL MECORD PLEASE RETURN TO AGENCY ARCHIVES, BLDG. A-18

Copy Nº

WARNING

This document contains information affecting the national defense of the United States, within the meaning of Title 18, sections 793 and 794, of the US Code, as amended. Its transmission or revelation of its contents to or receipt by an unauthorized person is prohibited by law.

GROUP 1
Excluded from automatic downstading and declarification

CENTRAL INTELLIGENCE AGENCY Directorate of Intelligence October 1969

Soviet Strategic Weapons: Background for SALT

Introduction

This handbook describes major Soviet strategic weapon systems which are of possible interest to the US delegation to strategit arms limitation talks (SALT). The information is for background use only and is not intended for direct introduction into discussions with the Soviets. Guidance on what may be discussed is available in the CIA memorandum Intelligence Guidance for US Delegation to Strategic Arms Limitation Talks. Background information on other weapon systems will be provided through the intelligence adviser for SALT.

The weapon systems described include guided missiles as well as missile-carrying submarines and strategic bombers. The characteristics, performance, and operational status of each system are briefly summarized. Special terms used in the descriptions are defined on the next page.

This handbook was produced solely by CIA. It was prepared by the Office of Strategic Research and coordinated with the Office of Scientific Intelligence and the Foreign Missile and Space Analysis Center.

Special Terms

Missiles

The data given for each missile include the year of its <u>initial operational capability</u> (IOC). By this date the first operational unit has been trained and equipped with a few weapons of the given type.

Circular error probability (CEP) indicates the accuracy of the weapon system, stated as the radius of a circle centered on the target. Statistically, half of all arriving warheads would impact within this circle.

Bombers

The <u>combat ceiling</u> indicated for each bomber is the greatest altitude at which the aircraft can continue to climb at the rate of 500 feet per minute, i.e. can maneuver effectively.


Radius is the maximum distance the bomber can cover to an objective allowing for return flight to the same base without refueling. This figure is reduced on missions in which tactical or other considerations require flight under less than ideal conditions.

Contents

	Page		Page
Intercontinental Ballistic Missiles		Other Surface-to-Surf Strategic Missiles	ace
SS-7 Saddler SS-8 Sasin SS-9 Scarp SS-X-6 SS-11 SS-13 Savage	1 2 3 4 5 6	SS-4 Sandal SS-5 Skean SS-14 Scamp SS-12 Scaleboard	. 7 8 9 10
Ballistic Missile S	ubmarines	and Associated Missil	es
Y Class	11	SS-N-6	12
H Class G Class Z-Conversion Class	13 14 15	SS-N-4 SS-N-5	16 17
Cruise Missile Sub	marines a	nd Associated Missiles	
E-II Class E-I Class J Class W-Conversion Class ("Long Bin") W-Conversion Class ("Twin Cylinder")	19 20 21 22 23	SS-N-3	24
Surface-to-Air and ABM Missiles			
SA-1 Guild SA-2 Guideline 26, SA-3 Goa SA-5 Gammon	25	ABM-1 Galosh	30
Strategic Bombers	and Air-	to-Surface Missiles	
TU-16 Badger M- Bison TU-22 Blinder TU-95 Bear	51 52 53 54	AS-2 Kipper AS-3 Kangaroo AS-4 Kitchen AS-5 Kelt	35 36 37 38

Intercontinental Ballistic Missile

SS-7 Saddler






IOC Configuration Propellant Launch weight Re-entry vehicle Warhead (nuclear)	1962 2-stage tandem storable liquid 325,000 lbs 3,500 ± 500 lbs 4,200 ± 500 lbs* 2,800 ± 400 lbs 3,300 ± 400 lbs*
Maximum range	$3,300 \pm 400 \text{ lbs*}$ 6,500 nm
Guidance CEP	5,500 nm* inertial 1.0-1.25 nm


*Two operational re-entry vehicles

First Soviet ICBM to be widely deployed. First flight test in October 1960.

Intercontinental Ballistic Missile

SS-8 Sasin







IOC	1963
Configuration	2-stage tandem
Propellant	nonstorable liquid
Launch weight	165,000 lbs
Re-entry vehicle	$3,500 \pm 500 \text{ lbs}$
Warhead (nuclear)	$2,800 \pm 400 \text{ lbs}$
Maximum range	6,000 nm
Guidance	radio-inertial
CEP	l nm

Probably given only limited deployment. First publicly displayed in Moscow parade of November 1964. First flight test in April 1961.

Intercontinental Ballistic Missile

SS-9 Scarp





IOC Configuration Propellant	1966 2-stage tandem storable liquid
Launch weight Re-entry vehicle	400,000 lbs 10,000 ± 500-1,000 lbs
Warhead (nuclear)	13,500 ± 500-1,000 lbs* 8,000 ± 1,000 lbs
Maximum range	11,000 ± 1,000 lbs* 7,000 nm
CEP Guidance	5,000 nm* (possibly 5,400 nm) 0.5-0.75 nm inertial with radio-
	inertial capability

^{*} Two operational re-entry vehicles

Largest and most accurate Soviet ICBM. Extensively deployed in USSR. First displayed in Moscow parade of November 1967. First flight test in December 1963. Also employed as launch vehicle for SS-X-6 and maneuverable satellites.

Depressed Trajectory
Intercontinental Ballistic Missile

SS-X-6


Configuration 2-stage and deboost Propellant storable liquid Launch weight 400,000 lbs Re-entry vehicle about 4,000 lbs about 3,200 lbs Warhead (nuclear) Maximum range about 6,000 nm Guidance inertial CEP 1-2 nm

SS-X-6 weapon system is composed of SS-9 ICBM and deboost stage with warhead. First flight test in December 1965. Operational status undetermined. As. DICBM, SS-X-6 in its current configuration is capable of striking US.

May also be used as fractional orbit bombardment system (FOBS) which places warhead in low earth orbit about 100 miles high. Deorbit engine kicks warhead out of orbit toward target before weapon has completed one revolution of earth. System lacks necessary energy to make it effective orbital weapon against US. Major changes in either warhead size or booster are necessary.

Intercontinental Ballistic Missile

SS-11




IOC	1966
Configuration	2-stage tandem
Propellant	storable liquid
Launch weight	93,000 lbs
Re-entry vehicle	$1,500 \pm 300 \text{ lbs}$
Warhead (nuclear)	1,200 ± 300 lbs
Maximum range	5,500 nm
Guidance	inertial
CEP	1.0 nm


Smallest Soviet ICBM tested to date. Deployed extensively throughout USSR. Never publicly displayed. First flight test in April 1965.



Intercontinental Ballistic Missile

SS-13 Savage







IOC	1969
Configuration	3-stage tanden
Propellant	solid
Launch weight	105,000 lbs
Re-entry vehicle	about 1,000 lbs
Warhead (nuclear)	about 750 lbs
Maximum range	about 5,000 nm
Guidance	
CEP	inertial
	1.0-1.5 nm

Estimated to become operational in fixed sites in 1969. First flight test in November 1965. First publicly displayed in Moscow parade of May 1965.

Medium-Range Ballistic Missile

SS-4 Sandal







IOC	1958
Configuration	single stage
Propellant	storable liquid
Launch weight	88,000 lbs
Re-entry vehicle	$3,300 \pm 500 \text{ lbs}$
Warhead (nuclear)	2,200 ± 500 lbs
Maximum range	1,020 nm
Guidance	inertial
CEP	1.25 nm

Deployed in both soft and hard sites located primarily in the European USSR. First publicly displayed in Moscow parade of November 1960. First flight test in June 1957. Much larger conventional warhead could be delivered to shorter ranges, e.g. about 4,000 lbs to 800 nm.

Intermediate-Range Ballistic Missile

SS-5 Skean







100	100
Configuration	1961
Propellant	single stage
Launch weight	storable liquid
Re-entry weight	about 200,000 lbs
	$3,500 \pm 500 \text{ lbs}$
Warhead (nuclear)	2,800 ± 400 lbs
Maximum range	2,200 nm
Guidance	inertial
CEP	0.5-0.75 nm

Deployed in both hard and soft sites located primarily in European USSR. First publicly displayed in Moscow parade of November 1964. First flight test in June 1960. Much larger conventional warhead could be delivered to shorter ranges, e.g. 8,000 lbs to 1,500 nm.

Intermediate-Range Ballistic Missile

SS-14 Scamp






IOC	1970
Configuration	2-stage tandem
Propellant	solid
Launch weight	about 35,000 lbs
	20046 33,000 108
Re-entry vehicle	1,200 ± 300 lbs
Warhead (nuclear)	900 ± 200 lbs
Maximum range	about 1,500 nm
Guidance	inertial
CEP	0.5-1.5 nm

Transporter-launcher first displayed in Moscow parade of May 1965. SS-14 missile first shown in November 1967. First flight test in September 1965. Probably will be deployed both in fixed sites and mobile launchers. Consists of second and third stages of SS-13 Savage.

Short-Range Ballistic Missile

SS-12 Scaleboard



IOC Configuration	4	٠,	1965 °
Launch wet.		- n	lb.
. <u> </u>			bs
warhead (HE, nucle	ar)	1,200	lbs
Maximum range		50	0 nm
Guidance		iner	tial
CEP	0	. 25 - 0.	

A mobile system designed to fill gap between 150-mile and 1,000-mile systems. Flight testing began in March 1964. May be deployed with front ground forces ment coverage of battle zone.




SS-12 probably is associated with Scaleboard mobile system (photograph) first displayed in November 1967.

SECRET -

Nuclear Powered Ballistic Missile Submarine - SSBN

Y Class






Date first unit operation	1967 ional 1968
Complement	about 100
Length	425 ft
Beam	38 ft
Displacement,	
surfaced	7,200 tons
submerged	8,700 tons
Propulsion	nuclear
Operating depth,	
normal	1,300 ft
collapse	2,000 ft
Submerged speed,	•
maximum	about 25 kts
Patrol radius,	,
O days on station	8,600 nm
20 days on station	5,800 nm
Patrol duration	60 days
Missiles	16 SS-N-6s
Torpedoes	3 2

This new Polaris type submarine is being built at two shipyards under a high priority program. As of mid-1969, five Y class units were operational and four additional units had been launched. The production program is estimated at 35 to 50 units.

Medium-Range Ballistic Missile

SS-N-6




LOC 1968 Configuration single stage Propellant storable liquid Launch weight unknown Re-entry vehicle 1,500 ± 500 1bs Warhead (nuclear) about 1,500 lbs Maximum range 1,300 nm Guidance inertial CEP about 1 nm

Carried by the 16-tube Y class ballistic missile submarine. Launched submerged.

Nuclear Powered Ballistic Missile Submarine - SSBN

H Class






Initial construction Number built	1959
Complement	100
Length	380 ft
Beam	30 ft
Displacement,	
surfaced	4,100 tons
	5,100 tons
Propulsion nuclear	(2 screws)
Operating depth,	
normal	1,000 ft
collapse	1,500 ft
Submerged speed, maximum	22 kt:
Patrol radius	
O days on station	8,600 nm
20 days on station	5,800 nm
Patrol duration	60 days
	5s in sail
Torpedoes	3 2

The eighth and last hull to be converted to fire the underwater-launched SS-N-5 now is undergoing this process. One of the nine units may have been converted to carry as many as six missiles of an undetermined type.

SECKET

Diesel Powered Ballistic Missile Submarine - SSB

G Class







Initial constru Number built Complement	ction 1958 23 85
Length	320 ft
Beam	28 ft
Displacement,	
surfaced	2,300 tons
submerged	2,800 tons
Propulsion	diesel (3 screws)
Operating depth	,
normal	l,000 ft
collapse	1,500 ft
Submerged speed	,
maximum	16 kts for 12 nm
economical	3 kts for 250 nm
Patrol radius	
0 days on sta	
20 days on st	
Patrol duration	
Missiles	3 SS-N-4s or SS-N-5s
Tr. I	in sail
Torpedoes	26

Eight units of this class have been converted to fire the underwater-launched SS-N-5, and four others are being converted. One unit was lost in the Pacific in 1968.

Diesel Powered Ballistic Missile Submarine - SSB

Z-Conversion Class






Initial coversion	1955
waent	80
ongth	295 ft
Beam	_
Displacement,	26 ft
surfaced	2,000 tons
submerged	2,400 tons
Propulsion d	iesel (3 screws)
Operating depth,	,
normal	750 ft
collapse	1,100 ft
Submerged speed,	-,
maximum	15 kts for 15 nm
economical	3 kts for 250 :
Patrol radius	
O days on station	3,600 nm
20 days on statio	
Patrol duration	60 days
Missiles	2 SS-N-4s
Torpedocs	26


Conversion of the Z class was the initial Soviet effort to equip a submarine with ballistic missiles. One unit of this class has had its missile tubes removed and been reconverted to a torpedo attack submarine.

SECKET

Short-Range Ballistic Missile

SS-N-4







100	1960
Configuration	single stage
Propellant	storable liquid
Launch weight	25,300 lbs
Re-entry vehicle	about 2,700 lbs
Warhead (nuclear)	about 2,200 lbs
Maximum range	350 nm
Guidance	inertial
CEP	1 - 2 nm

Launched from G-I and converted Z class submarines. Submarine surfaces prior to launch. Was also launched from H-I class submarines. First confirmed public appearance in Murmansk parade in November 1967. May have been shown on Soviet-East European TV and movies since 1965.

Medium-Range Ballistic Missile

SS-N-5





(Possible SS-N-5)

IOC	1963
Configuration	single stage
Propellant	storable liquid
Launch weight	39,000 lbs
Re-entry vehicle	2,800 ± 500 lbs
Warhead (nuclear)	2,200 ± 500 lbs
Maximum range Guidance	700 nm
CEP	inertial
	1-2 nm


Launched submerged from $G\text{-}\!AII$ and $H\text{-}\!AII$ class submarines.

SPORTTS

18

Nuclear Powered Cruise Missile Submarine - SSGN

E-II Class






Initial construction	1962
Number built	28
Complement	100
Length	385 ft
Beam	30 ft
Displacement,	30 11
surfaced	4,200 tons
submerged	5,200 tons
Propulsion nuclear	(2 screws)
Operating depth,	,
normal	1,300 ft
collapse	2,000 ft
Submerged speed, maximum	23 kts
Patrol radius	20 863
O days on station	8,600 nm
20 days on station	5,800 nm
Patrol duration	60 days
Missiles	•
	8 SS-N-3s
Torpedoes	2 2

This class was built in Northern and Pacific Fleet shippards.

Nuclear Powered Cruise Missile Submarine - SSGN

E-I Class



Missile launching tubes in elevated position


Initial construction Number built	1960
Complement	100
Length	375 ft
Beam	30 ft
Displacement,	
surfaced	4,000 tons
submerged	5,000 to:
	(2 screws,
Operating depth,	
normal	1,000 ft
collapse	1,500 ft
Submerged speed, maximum	24 kts
Patrol radius	
O days on station	8,600 nm
20 days on station	5,800 nm
Patrol duration	60 days
Missiles	6 SS-N-3s
Torpedoes	22

All E-I class submarines were built in Pacific Fleet shippards.

SEGRET

Diesel Powered Cruise Missile Submarine - SSG

J Class





Initial construction Number built Complement Length Beam	1962 16 80 280
Displacement,	
surfaced	2,700 tons
submerged	3,500 tons
Propulsion diesel	(2 screws)
Operating depth,	•
normal	1,300 ft
collapse	2,000 ft
Submerged speed,	,
•	for 14 nm
economical 2.8 kts	
Patrol radius	
O days on station	3,600 nm
20 days on station	2,400 nm
Patrol duration	60 days
Missiles	4 SS-N-3s
Torpedoes	22

Construction of this class has ended.

SEGRET,

Diesel Powered Cruise Missile Submarine - SSG

W-Conversion Class ("Long Bin")



19 Initial constriction Number built 60 Complement 275 ft Length 23 ft Beam Displacement, 1,200 tons surfaced 1,500 tons submerged diesel (? Propulsion Operating depth, 336 ft normal 984 ft collapse Submerged speed, 12 kts for 12 nm maximum economical 2.5 kts for 300 nm Patrol radius 2,400 nm O days on station 1,200 nm 20 days on station 40 days Patrol duration 4 SS-N-3s Missiles Torpedoes 10

Basically a W class hull with a 25-ft section added, a new sail, and four missile launchers.

SECRET -

Diesel Powered Cruise Missile Submarine - SSG

W-Conversion Class ("Twin Cylinder")






Initial construction 19 Number converted Complement	5
	56
Length 249	
Beam 23	ft
Displacement,	
surfaced 1,100 to	n s
submerged 1,400 to	n s
Propulsion diesel (2 screws	
Operating depth,	- ,
normal 656	ft
collapse 984	
Submerged speed,	LC
	n m
2.5.1	
Patrol radius	n m
0 1	
20 1	
20 days on station 1,200	
Patrol duration 40 day	
Missiles 2 SS-N-	3 s
Torpedoes	1 2

Standard W class fitted with two missile launchers aft of the sail.

Naval Cruise Missile

SS-N-3




100 1961 Propulsion rocket-boosted turbojet Launch weight 10,000 lbs Warhead (HE, 1,000-2,000 lbs chemical, nuclear) 250 nm Maximum range 1,000-3,000 ft Cruising altitude Cruising speed Mach 0.9-1.6 Guidance preset autopilot/command override/terminal homing


Carried by diesel powered J and modified W class submarines, nuclear powered E-I and E-II submarines, and Kynda and Kresta class cruisers. Submarines must surface to launch.

In primary role as antiship missile, maximum operational range is 250 nm when launched from submarine and 150 nm from surface ship. This weapon could also be used against land targets.

Surface-to-Air Missile

SA-1 Guild







IOC1954 Propulsion single-stage liquid Warhead (HE or nuclear) 465 lbs Maximum operational range 18-24 nm Effective altitude, maximum 60,000-80,000 ft minimum 3,500 ft Speed Mach 5 Guidance command CEP 100-200 ft

Introduced in 1954 as part of fixed Moscow area defenses. Not deployed elsewhere.

Surface-to-Air Missile

SA-2 Guideline Mod 1, 2






100	Mod	1	1959, Mod 2 1960
Propulsion			solid booster,
			liquid sustainer
Warhead (HE)			420. 1bs
Maximum opera-			Mod 1 19 nm
tional range			Mod 2 24 nm
Effective alti	tude	,	
maximum			80,000-90,000 ft
minimum			Mod 1 1,500 ft
•			Mod 2 1,000 ft
Speed			about Mach 4
Guidance			command
CEP			75-100 ft


No external features have been identified to distinguish Mod 1 from Mod 2. Mod 1 is employed with Fan Song B S-band radar, Mod 2 with Fan Song C C-band radar. Mod 1 no longer operational in USSR. Exported to Warsaw Pact and many other countries. Mod 2 still operational in USSR.

Surface-to-Air Missile

SA-2 Guideline Mod 3, 4



(Mod 4)



IOC Mod 3 1962, Mod 4 1966 Propulsion solid booster, liquid sustainer Warhead (Mod 3 HE, Mod 4 nuclear) about 420 lbs Maximum operational range 27 nm Effective altitude, maximum 90,000 ft minimum 1,000 ft Speed about Mach 4 Guidance command CEP about 50 ft


Primary weapon of Soviet SAM forces. Employed with Fan Song E C-band radar.


Mod 3 exported to most Warsaw Pact countries and Yugoslavia. Also deployed with Soviet forces in Eastern Europe and Mongolia.

Mod 4 first displayed in November 1967. Probably deployed only in USSR.

Surface-to-Air Missile

SA-3 Goa






IOC Propulsion solid booster & sustainer Warhead (HE) 140 lbs Maximum operational range about 13 nm Effective altitude, maximum about 50,000 ft minimum about 500 ft Speed Mach 2.5 Guidance command CEP about 30 ft

Deployed around Moscow and Leningrad, and in many border areas of USSR. Deployment is continuing. Also deployed at Soviet tactical airfields in East Germany, Poland, and Hungary.

Long-Range Surface-to-Air Missile

SA-5 Gammon





IOC 1967 Propulsion solid booster, liquid sustainer Warhead (HE) 700-750 lbs Maximum operational range 50-100 nm Effective altitude, maximum 110,000 ft minimum unknown Speed Mach 4.5 Guidance command/terminal homing CEP 100 ft

Designed to defend against medium and high altitude aircraft and standoff weapons. Deployed extensively throughout USSR. Never publicly displayed.

ABM Missile

ABM-1 Galosh





IOC 1968 Propulsion solid booster with probable liquid sustainer/ terminal propulsion stage Warhead (nuclear) 2,000-3,000 1bs Maximum operational range 350 nm Effective altitude, maximum 200-300 nm minimum 50,000 ft Speed 11,500-14,500 ft per second Guidance probably command type using small Try Add radars

Deployment limited to Moscow area. Estimated to provide limited defense capability against ballistic missile attack.

Strategic Bomber

TU-16 Badger




Engines	2, jet
Span	108 ft
Length	119 ft
Radius	1,650 nm
Maximum speed	540 kts
Cruise speed	445 kts
Combat ceiling	44,800 ft
Crew	5 - 6
Bomb capacity	20,000 lbs
Normal bomb load	6 600 lbs

Badger A (1956	in service with Soviet long range,
	naval, and air defense air forces.
-Badger B (1957	
	air-to-surface missiles.
Badger C (1960) Converted to carry one AS-2 Kipper
	air-to-surface missile.
Badger D (1964) Electronic reconnaissance aircraft.
-Badger E (1963	 Photographic reconnaissance aircraft.
Badger F (1963	Electronic and photographic recon-
	naissance aircraft.
Badger G	Converted to carry two AS-5 Kelt
(1965-66	

Strategic Bomber

M- Bison




Engines	4, jet
Span	170 ft
Length	160 ft
Radius	3,050 nm
Maximum speed	545 kts
Cruise speed	445 kts
Combat ceiling	47,100 ft
Crew	8
Bomb capacity	30,800 lbs
Normal bomb load	10,000 lbs

Bison A (1955)	Soviet long range air force strategic
Bison B (1957)	heavy bomber and aerial tanker. Increased fuel load, improved engines
Bison C (1960)	and radar. Slight structural modifications.

Strategic Bomber

TU-22 Blinder




Engines	2,	af	terbur	n i	n	g	j	e t
Span .	•							f t
Length					l	3 :	l	ft
Radius				1	, 8	0 ()	nm
Maximum sp	eed			(7	5	k	ts
Cruise spe								ts
Combat cei	lin	g	5	3	, l	0 (Э	£t
Crew								3
Bomb capac	ity	,						bs
Normal bom	ıb 1	oa	d 6	, (50	()]	lb s

Blinder A (1962)	Supersonic medium bomber of the Soviet long range and naval air
Blinder B (1967)	forces. Modified to carry one AS-4 Kitchen
Blinder C (1966)	air-to-surface missile. Electronic reconnaissance aircraft.

Strategic Bomber

TU-95 Bear





Engines	4,	turboprop with
	1	counterrotating
		propellers
Span		165 ft
Length		147 ft
Radius		4,500 nm
Maximum spee	d	500 kts
Cruise speed		435 kts
Combat ceili	n g	41,100 ft
Crew	_	8
Bomb capacit	y	30,000 lbs
Normal bomb	10	ad 10,000 lbs

Bear A (1956)	Strategic heavy bomber of the Soviet
	long range air forces.
Bear B (1960)	Modified to carry one AS-3 Kangaroo
	air-to-surface missile.
Bear C (1962)	Same as B model but with additional
	electronic equipment.
Bear D (1965)	Electronic reconnaissance aircraft
	of the Soviet naval air forces.
Bear E (1965)	Photographic reconnaissance aircraft.

Air-to-Surface Missile

AS-2 Kipper







IOC	1960 - 61
Propulsion	turbojet
Launch weight	9,100 lbs
Warhead (HE, nucl	
Range	110 nm
Launch speed, at	
Maximum cruise sp	
high altitude	Mach 1.7
low altitude	Mach 1.2
Guidance a	utopilot with command
	rride/terminal homing
CEP, against ships	
against land	targets 1-2 nm
Carrier:load	TU-16 Badger C : one

Used only by Soviet naval air forces, primarily in antiship role.

Air-to-Surface Missile

AS-3 Kangaroo







IOC	1960-61				
Propulsion					
•	turbojet				
Launch weight	25,000 lbs				
Warhead (nuclear)	4,500-5,500 lbs				
Maximum range	275-350 nm				
Speed	Mach 1.8-2.0				
Guidance	autopilot with				
	command override				
CEP	1 - 3 nm				
Carrier:load T	U-95 Bear B,C : one				

Designed as standoff weapon for strategic attack against large land targets.

Air-to-Surface Missile

AS-4 Kitchen






IOC 1968 Propulsion liquid rocket Launch weight 14,000 lbs Warhead (HE, nuclear) 2,200 lbs Range, against ships 230 nm against land targets 300 nm Speed Mach 3.5 Guidance unknown CEP 1-2 nm Carrier:load TU-22 Blinder B : one

Apparently designed for use against land and ship targets.

Air-to-Surface Missile

AS-5 Kelt



IOC1963-65 Propulsion liquid-fuel rocket Launch weight about 6,000 lbs Warhead (HE, nuclear) 1,000-2,000 lbs Range 80-120 nm Speed Mach .9-1.2Guidance unknown, possibly preset autopilot with command override/possibly terminal homing in antiship role CEP, against land targets 1 - 2 nm against ships 150 ft Carrier:load TU-16 Badger G : two

Launch occurs at altitude of 30,000-35,000 feet at about 440 knots. Began to replace AS-1 about 1963. Has extended the useful life of TU-16 Badger B.

